# Hisense



# 50DM66D 50" 4K UHD DIGITAL SIGNAGE DISPLAY

Hisense Digital Signage is designed to serve multiple business applications: public spaces, transportation systems, museums, stadiums, retail stores, hotels, restaurants and corporate buildings. With DM series, it delivers powerful engagement from any devices, boost business with real-time updates, data-driven insights and visually appealing content, manage and control devices at anytime from anywhere, and simplify the cable management by conecting a series of displays to a single video output.

# Highlights



## Narrow Bezel

With a narrow bezel and symmetrical design, the display can be easily integrated into any environment. All terminals face outwards, ensuring the display hangs flush against the wall which saves space and facilitates installation.



#### **Clean Cable Solution**

The integrated cable holder hides cables and keeps the back of the display tidy and uncluttered. This reduces visual distractions that can get in the way of your viewing experience.



# Wireless Screen Sharing

Everthing you need for screen sharing solutions. ScreenShare is a in house built-in screen sharing application that enables the screen sharing wirelessly and seemlessly from anywhere and from any devices.



## Mobile Device Management

VisionInfo is a cloud-based device managemet software that offers end-to-end device management and control through all devices. It is a powerful, effective and easy to use tool to control your devices at anytime from anywhere.









## Android 11

Android 11 works to keep your data safe and secure. With Android 11, you have more control over what information apps can and can't access. Devices that work better together, enhance your messaging, audio and multitasking experiences.



# **Anti-glare Coating**

All DM Series displays offer higher haze panels that help reduce reflections without adversley affecting the image quality. Anti-glare coatings can also improve the perceived contrast of the display.

# **Smart Power**

The backlight intensity can be controlled and pre-set by the system to reduce the power consumption, ENERGY STAR-certified, the display helps you protect the environment and save costs.



# **Conformal Coating**

Electronic components are completely protected from the environmental factors like moisture, dust, salt, chemicals, temperature changes and mechanical abrasion.

# Hisense

# Specifications

# Digital Display Panel

Backlight Type	DLED	
Туре	VA	
Size	50"	
Resolution	3840 x 2160	
Refresh rate	60Hz	
Color Depth	1.07G (8 Bits+FRC)	
Brightness(Typ.)	500 nits	
Contrast Ratio(Typ.)	5000:1	
Response Time(Typ.)	8ms	
Viewing Angle(Min.)	178°/178°	
Color Gamut(Typ.)	DPI-P3 92%	
Haze	25%	
Orientation	Landscape & Portrait	
Lifetime	up to 50,000 hrs	
Operation Hours	7Day x 24Hour	

### System

Operating System	Android 11
Processor CPU	ARM Cortex-A55 Quad core
Processor GPU	Mali-G52
Memory	3G DDR4
Storage	32G EMMC
Language	Simplified Chinese/English/French/ German/Polish/Spanish/Russian/ Italian/Finnish/Norwegian/Swedish/ Hebrew/Arabic/Thai/Malay/Indonesian

# Connectivity

WI-FI Bluetooth	2.4/5.0GHz dual,802.11a/b/g/n/ac BT5.1
Input	HDMI(2.0) x 2 DP(1.2a) x 1 USB2.0(A) x 1 USB3.0(A) x 1 RS232(RJ45) x 1 LAN(RJ45) x 1
Output	HDMI x 1 Audio(3.5mm) x 1 RS232(RJ45) x 1


#### Physical

Bezel Color	Black
Set Dimension(W×H×D )	1124.1 x 644.2 x 62.5mm 44.26 x 25.33 x 2.46inch
Bezel width(T/L/R/B)	10.4mm(T/L/R), 11.1mm(B)
Net Weight	11kg / 24.3lbs
Packing Dimension (W×H×D)	1251 x 777 x 154mm 49.3 x 30.6 x 6.1inch
Gross Weight	16.2kg / 35.7lbs
VESA Mount	300mm x 300mm

Power		
Power Supply		AC 100~240V (50/60Hz)
Power Consumption (Ma	ax.)	175W
Standby Consumption		<0.5W (Standby Mode)
Speaker		
Built in speaker		10W x 2
Environment		
Operating Temperature		0°~40°C
Operating Humidity		10%~80% Non-Condensing
What's in the box	x	
		Quick Setup Guide
		Warranty Card
Standard		Power Cord
		Remote Controller
		Batteries
		RS232(in) Gender
Certification		
Standard Certification	CCC/CB/CE/FCC/cTUVus/UKCA/CEC/ERP	
Safety	62368-1	
Enviroment	Energy Star 8.0	energy
IP Rating	IP5X	ENERGY STAR

### Dimensions

**50**" 1124.1 x 644.2 x 62.5mm / 44.26 x 25.33 x 2.46inch 11kg / 24.3lbs



Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.

Learn More: www.hisense-b2b.com | Contact Us: sales@hisense-b2b.com

# Hisense COMMERCIAL

💼 @Hisense B2B Europe | @Hisense B2B USA | @Hisense B2B MENA | @Hisense B2B Indonesia | @Hisense B2B South Africa | @Hisense B2B Australia